

Selection Guide

PC/104 CPU Boards

DELTA COMPONENTS GmbH

Auweg 27 * D-79761 Waldshut-Tiengen

Tel.: +49 (0) 7751 / 8399-0

Fax: +49 (0) 7751 / 8399-99

info@delta-components.de

www.delta-components.de

www.automotive-computing.com

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

13 Artikel aus dem Bereich
PC/104 CPU Boards
wurden für das PDF ausgewählt.

Selection Guide PC/104 CPU Boards



CoreModule 920 PCI/104e



CoreModule 430 PC/104



CoreModule 1-86DX3 PC/104

TouchScreen			
PC/104 (96 x 90 mm)	-	x	x
PC/104-Plus (96/99 x 90 mm)	-	-	-
PCI/104	-	-	-
PCI/104-Express (96/99 x 90/117mm)	x	-	-
PCle/104	-	-	-
Cooling System	-	-	Passive
CPU	Dual-Core 3rd Gen. Intel Core i7-3517UE / Single-Core 3rd Gen. Intel Celeron 807UE	Vortex86X 300MHz, Vortex86DX 800MHz	Vortex 86DX3, 1.0 GHz
CPU Socket	-	-	-
FSB Frequency	1.066MHz	-	-
Chipset	Intel QM67	-	-
BIOS	AMI EFI	AMI BIOS	AMI BIOS
Watchdog Timer	x	x	x
Controller	-	PC-compatible DMA and interrupt controller and timers	-
Basic Equipment	2GB	256MB	2GB
Maximum Equipment	4GB	-	-
DRAM	-	x	DDR3L
SDRAM	DDR3	-	-
DIMM / MemorySocket	-	-	-
CD-ROM	-	-	-
Compact Flash	-	1x	-
SD	-	-	-
HDD	-	-	-
HD SATA	2x	-	1x SATA
HD PATA	-	PATA100 IDE	-
Removeable Storage	-	-	-
Graphic Interface	1x VGA/CRT, 1x HDMI, 1x LCD-LVDS	-	1x VGA/CRT, 1x LCD-TTL
Interface COM	2x RS232	2x RS232/422/485	2x RS232, 2x RS232/422/485
CAN	-	-	-
Interface USB	4x USB 2.0	2x USB 2.0	2x USB 2.0
Interface LAN	2x 10/100/1000 BASE-T	1x 10/100 BASE-T	1x 10/100 BASE-T, 1x 10/100/1000 BASE-T
Interface IO	-	8x GPIO	8x GPIO
Mini PCIe	-	-	-
Mini PCI	-	-	-
Encoding	full HW MPEG2	-	-
Decoding/Playback	HW JPEG & MJPEG	-	-
Bluetooth	-	-	-
LPT	-	-	-
PS/2	-	-	1x
Sound	-	-	-
Audio	(High Definition Audio)HDA	-	-
Speakers	-	-	-
Headphone	-	-	-
Console Port	-	-	-
SIM Card	-	-	-
GPS	-	-	-
Mobile Communication 3G	-	-	-
PCI	1x PCI x16	-	-
PCle	4x PCle x1	-	-
ISA	-	x	x
PC/104	-	-	x
PC/104-Plus	-	-	-
PCI/104	-	-	-
PCI/104-Express	-	-	-
Video File Format	-	-	-
Max. Video Resolution	-	-	-
Operating System Support	Windows7, Linux, WES7, WES2009, WEC7, vxworks6.9, QNX6.5	QNX v6.3, Windows CE5.0/6.0	WES7/9, Linux, QNX, WEC7 and WinCE6.0
Input Voltage Nominal	5VDC (3.3V and 12V required by PC/104 Express)	5 VDC	5VDC
Input Voltage Min/Max	-	-	-
Input Current	9W	-	Approx. 6 to 7W
Power Management	-	-	-
Battery	-	-	-
Operating Temperature	-20°C to 70°C	-20°C to 70°C	0°C to 60°C
Extended Operating Temperature	-40°C to 85°C	-40°C to 85°C	-40°C to 85°C
Storage Temperature	-55°C to 85°C	-55°C to 85°C	-55°C to 85°C
Relative Humidity	90% at 60°C, non-condensing	-	10% to 90%, non-condensing
MTBF	-	-	-
Certification	-	-	-
Dimensions	116 x 96 mm	-	96 x 90 mm
Weight	-	-	-
Typ. Application	Industrial, Military	Industrial	Industrial

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

13 Artikel aus dem Bereich
PC/104 CPU Boards
wurden für das PDF ausgewählt.

Selection Guide PC/104 CPU Boards



CoreModule 920 PCI/104e



CoreModule 430 PC/104



CoreModule 1-86DX3 PC/104

Bestellinformation			
	Artikel-Nr. PPAS7804 CoreModule 920- PC/104-Express 3rd Generation SBC, Celeron 807UE 1.0GHz, 2GB DDR3, 8GB SSD, PCI Artikel-Nr. PAS7804-1 Quick Start Kit incl. CoreModule 920- PC/104-Express 3rd Generation SBC , PPAS7804, Cable kit, copper heatsink, QuickDrive + manual Artikel-Nr. PPAS7805 CoreModule 920- PC/104-Express 3rd Generation SBC, Core i7-3517UE 1.7GHz, 2GB DDR3, 8GB SSD, PCI, PCIe Artikel-Nr. PPAS7805-1 Quick Start Kit incl. CoreModule 920- PC/104-Express 3rd Generation SBC , PPAS7805, Cable kit, copper heatsink, QuickDrive + manual Artikel-Nr. PPAS7805-2 CoreModule 920- PC/104-Express 3rd Generation SBC, Core i7-3517UE 1.7GHz, 4GB DDR3, 8GB SSD, PCI, PCIe	Artikel-Nr. PPAS7000 CoreModule 430 - PC/104 Single Board Computer, Vortex 86SX 300MHz, soldered RAM 256MB, -20°-70°C Artikel-Nr. PPAS7000-1 CoreModule 430 - PC/104 Single Board Computer, Vortex 86SX 300MHz, soldered 256MB, Video, -20°-70°C Artikel-Nr. PPAS7000-2 CoreModule 430 - PC/104 Single Board Computer, Vortex 86DX 800MHz, soldered RAM 256MB, -20°-70°C	Artikel-Nr. PPAS7010 CoreModule 1-86DX3, PC/104 Single Board Computer, Vortex 86DX3 1GHz, 2GB DDR3L, 0°C to 60°C Artikel-Nr. ,

Bitte laden Sie sich bei Bedarf [hier](#) eine aktualisierte Fassung dieses Dokuments herunter!

13 Artikel aus dem Bereich
PC/104 CPU Boards
wurden für das PDF ausgewählt.

Selection Guide PC/104 CPU Boards



CoreModule 1-86DX2 PC/104



TinyATOM E3800



MicroATOM E3800

TouchScreen			
PC/104 (96 x 90 mm)	x	-	-
PC/104-Plus (96/99 x 90 mm)	-	-	-
PCI/104	-	-	-
PCI/104-Express (96/99 x 90/117mm)	-	x	x
PCIe/104	-	-	-
Cooling System	Passive	-	-
CPU	Vortex86DX2, 800/1.000 MHz	4th generation E3800 series Intel® Atom Processor, Dual Core, 1.46GHz, 1MB L2 Cache	4th gen. E3800 series Intel® Atom Processor, Dual Core, 1.33GHz, 1MB L2 Cache
CPU Socket	-	-	-
FSB Frequency	-	-	-
Chipset	-	-	-
BIOS	AMI BIOS	-	-
Watchdog Timer	x	-	-
Controller	-	-	-
Basic Equipment	512MB or 1GB	4GB	2GB
Maximum Equipment	-	-	-
DRAM	DDR2	-	-
SDRAM	-	DDR3L	DDR3L
DIMM / MemorySocket	-	-	-
CD-ROM	-	-	-
Compact Flash	-	-	16GB eMMC Flash
SD	1x MicroSD	-	-
HDD	-	-	-
HD SATA	1x SATA (or 1x mSATA)	1x standard SATA 3Gb/s	1x standard SATA 3Gb/s
HD PATA	-	-	-
Removeable Storage	-	-	-
Graphic Interface	1x VGA/CRT, 1x LCD-LVDS	DVI, HDMI, Dual-channel 24bit LVDS LCD-LVDS	-
Interface COM	2x RS232/485, 2x RS232/485 (Optional)	1x RS-232	1x RS-232
CAN	-	-	-
Interface USB	3x USB 2.0	4x USB 2.0, 1x USB 3.0	4x USB 2.0
Interface LAN	1x 10/100 BASE-T, Optional 10/100/1000 BASE-T	10/100/1000 BASE-T	10/100/1000 BASE-T
Interface IO	8x GPIO	-	-
Mini PCIe	-	1x	1x
Mini PCI	-	-	-
Encoding	-	-	-
Decoding/Playback	-	Video decode HW acceleration for H.264, MPEG2, VC1, VP8	-
Bluetooth	-	-	-
LPT	1x	-	-
PS/2	1x	-	-
Sound	HD Audio (optional)	Intel® HD Audio controller	Intel® HD Audio controller
Audio	-	Stereo-Out, Stereo Line-In, Stereo Mic-In	Stereo-Out, Stereo Line-In, Stereo Mic-In
Speakers	-	-	-
Headphone	-	-	-
Console Port	-	-	-
SIM Card	-	-	-
GPS	-	-	-
Mobile Communication 3G	-	-	-
PCI	-	-	-
PCIe	PCIeMini	-	-
ISA	x	-	-
PC/104	x	-	-
PC/104-Plus	-	-	-
PCI/104	-	Up to 4x	Up to 4x
PCI/104-Express	-	4x	4x
Video File Format	-	-	-
Max. Video Resolution	-	Up to 1.920 x 1.200	-
Operating System Support	Windows XP/XPe, Linux	Windows 7 / 8, Linux	WINDOWS 10 / 8 / 7, Linux
Input Voltage Nominal	5VDC	+5V	+5V
Input Voltage Min/Max	-	-	-
Input Current	Approx. 6 to 7W	-	12W
Power Management	-	-	-
Battery	-	-	-
Operating Temperature	Standard: 0°C to 60°C Industrial: -20°C to 70°C	0°C to 60°C	-
Extended Operating Temperature	-40°C to 85°C	-40°C to 85°C	-40°C to 85°C
Storage Temperature	-55°C to 85°C	-	-
Relative Humidity	10% to 90%, non-condensing	5% to 95% non-condensing (optional conformal coating)	5% to 95% non-condensing (optional conformal coating)
MTBF	-	-	-
Certification	-	-	-
Dimensions	96 x 90 mm		
Weight	-		
Typ. Application	Industrial	Industrial	Industrial

Selection Guide PC/104 CPU Boards



CoreModule 1-86DX2 PC/104



TinyATOM E3800



MicroATOM E3800

Bestellinformation

Artikel-Nr. PPAS7003
CoreModule 1-86DX2, PC/104 Single Board
Computer, Vortex 86DX2 1GHz, 1GB DDR2, 0°C
to 60°C

Artikel-Nr. PPAS7003-1
CoreModule 1-86DX2, PC/104 Single Board
Computer, Vortex 86DX2 1GHz, 1GB DDR2,
-20°C to 70°C

Artikel-Nr. PPAS7003-2
CoreModule 1-86DX2, PC/104 Single Board
Computer, Vortex 86DX2 1GHz, 512MB DDR2,
0°C to 60°C

Artikel-Nr. PPAS7003-3
CoreModule 1-86DX2, PC/104 Single Board
Computer, Vortex 86DX2 1GHz, 512MB DDR2,
-20°C to 70°C

Artikel-Nr. PPAS7004
CoreModule 1-86DX2, PC/104 Single Board
Computer, Vortex 86DX2 800 MHz, 1GB DDR2,
-40°C to 85°C

Artikel-Nr. PPAS7004-1
CoreModule 1-86DX2, PC/104 Single Board
Computer, Vortex 86DX2 800 MHz, 512MB DDR2,
-40°C to 85°C

Artikel-Nr. PPAS6007
TinyAtom E3800, PCI/104e SBC, 0°C to 60°C,
IntelAtom E3800 DualCore 1.46GHz, 4GB DDR3L,
8GB eMMC, supports two independent displays
(HDMI/DVI)

Artikel-Nr. PPAS6007-1
TinyAtom E3800-EXT, PCI/104e SBC, -40°C to
85°C, IntelAtom E3800 DualCore 1.46GHz, 4GB
DDR3L, 8GB eMMC, supports two independent
displays (HDMI/DVI)

Artikel-Nr. PPAS6008-1
MicroATOM-DC/16G-EXT, PCI/104e SBC, -40°C
to 85°C, IntelAtom E3800 DualCore 1.33GHz, 2GB
DDR3L, 16GB eMMC

Bitte laden Sie sich bei Bedarf [hier](#) eine aktualisierte Fassung dieses Dokuments herunter!

13 Artikel aus dem Bereich
PC/104 CPU Boards
wurden für das PDF ausgewählt.

Selection Guide PC/104 CPU Boards



Cool LiteRunner Eco PC/104



CoreModule 3-BT4 PCI/104+



CoreModule 3-BT1 PCI/104

TouchScreen	-	-	-
PC/104 (96 x 90 mm)	x	x	-
PC/104-Plus (96/99 x 90 mm)	-	-	-
PCI/104	-	-	x
PCI/104-Express (96/99 x 90/117mm)	-	-	-
PCIe/104	-	-	-
Cooling System	-	-	-
CPU	Intel Atom Z530 1.6GHz/ Intel Atom Z510 1.1GHz	Intel Atom E3845 (4C), 1.91 GHz	Intel Atom E3815 (1C), 1.46 GHz
CPU Socket	-	-	-
FSB Frequency	-	-	-
Chipset	-	-	-
BIOS	Award BIOS	AMI EFI	AMI EFI
Watchdog Timer	x	x	-
Controller	-	SEMA Board Controller	SEMA Board Controller
Basic Equipment	-	-	-
Maximum Equipment	2 GB	4GB	4GB
DRAM	-	-	-
SDRAM	-	-	-
DIMM / MemorySocket	-	DDR3L SO-DIMM	DDR3L SO-DIMM
CD-ROM	-	-	-
Compact Flash	-	-	-
SD	1x Micro SD	-	-
HDD	-	-	-
HD SATA	2x SATA II	1x (optional 2nd SATA 3GB/s port)	1x
HD PATA	-	-	-
Removeable Storage	-	-	-
Graphic Interface	1x VGA/CRT, 1x LCD-LVDS	VGA/CRT, LCD-LVDS	VGA/CRT, LCD-LVDS
Interface COM	2x RS232/422/485	2x RS232/485, 2x RS232/485 (Optional)	2x RS232/485, 2x RS232/485 (Optional)
CAN	-	-	-
Interface USB	6x USB	3x (1x on mSATA) USB 2.0	3x USB 2.0
Interface LAN	2x 10/100/1000 BASE-T	10/100/1000 BASE-T	10/100/1000 BASE-T
Interface IO	8x GPIO	8x GPIO	8x GPIO
Mini PCIe	1x	-	-
Mini PCI	-	-	-
Encoding	-	-	-
Decoding/Playback	-	-	-
Bluetooth	-	-	-
LPT	1x	-	-
PS/2	1x	-	-
Sound	High Definition Audio (HDA)	ALC886	ALC886
Audio	Line-In, Line-Out, Mic, SPDIF	-	-
Speakers	-	-	-
Headphone	-	-	-
Console Port	-	-	-
SIM Card	-	-	-
GPS	-	-	-
Mobile Communication 3G	-	-	-
PCI	-	-	-
PCIe	1x Mini-PCIe	-	-
ISA	-	-	-
PC/104	-	x	x
PC/104-Plus	-	-	-
PCI/104	-	-	-
PCI/104-Express	-	-	-
Video File Format	-	-	-
Max. Video Resolution	-	-	-
Operating System Support	Windows XP, XP E,bedded, Windows CE, Linux,DOS	Standard Support: Windows 7/8, 32/64-bit, Linux 32/64-bit, WES7/8, WEC7, QNX, VxWorks Extended Support (BSP): WES7/8, WEC7, Linux, QNX, VxWorks	Standard Support: Windows 7/8 32/64-bit, Linux 32/64-bit, WES7/8, WEC7, Linux, QNX, VxWorks
Input Voltage Nominal	5VDC	5VDC	5VDC
Input Voltage Min/Max	-	-	-
Input Current	11W	-	-
Power Management	-	-	-
Battery	Battery onboard	-	-
Operating Temperature	Commercial: 0°C to 60°C Industrial: -20°C to 60°C	0°C to 60°C	0°C to 60°C
Extended Operating Temperature	-40°C to 85°C	-40°C to 85°C	-40°C to 85°C
Storage Temperature	-	-	-
Relative Humidity	-	5-90% RH operating, non-condensing; 5-95% RH storage (and operating with conformal coating)	5-90% RH operating, non-condensing
MTBF	333.291 hrs at 25°C	-	-
Certification	-	-	-
Dimensions	-	90 x 96mm	-
Weight	-	-	-
Typ. Application	Industrial	Industrial	Industrial

Selection Guide PC/104 CPU Boards



Cool LiteRunner Eco PC/104



CoreModule 3-BT4 PCI/104+



CoreModule 3-BT1 PCI/104

Bestellinformation			
	Artikel-Nr. PPAS7201 Cool LiteRunner-ECO - PC/104 Single Board Computer, Atom Z510 1.1GHz, 1GB RAM, 0° - +60°C Artikel-Nr. PPAS7201-1 Cool LiteRunner-ECO - PC/104 Single Board Computer, Atom Z510 1.1GHz, 1GB RAM, -20° - +60°C Artikel-Nr. PPAS7201-2 Cool LiteRunner-ECO - PC/104 Single Board Computer, Atom Z510 1.1GHz, 1GB RAM, -40° - +85°C Artikel-Nr. PPAS7202 Cool LiteRunner-ECO - PC/104 Single Board Computer, Atom Z530 1.6GHz, 1GB RAM, 0°-60°C Artikel-Nr. PPAS7202-1 Cool LiteRunner-ECO - PC/104 Single Board Computer, Atom Z530 1.6GHz, 1GB RAM, -20° - +60°C Artikel-Nr. PPAS7202-2 Cool LiteRunner-ECO - PC/104 Single Board Computer, Atom Z530 1.6GHz, 1GB RAM, -40° - +85°C Artikel-Nr. PPAS7203 Cool LiteRunner-ECO - PC/104 Single Board Computer, Atom Z530 1.6GHz, 2GB RAM, 0° - +60°C Artikel-Nr. PPAS7203-1 Cool LiteRunner-ECO - PC/104 Single Board Computer, Atom Z530 1.6GHz, 2GB RAM, -20° - +60°C Artikel-Nr. PPAS7203-2 Cool LiteRunner-ECO - PC/104 Single Board Computer, Atom Z530 1.6GHz, 2GB RAM, -40° - +85°C	Artikel-Nr. PPAS7207 CoreModule 3-BT4, PCI/104+ Single Board Computer, Intel Atom E3845 1.91GHz, up to 4GB DDR3L, 0°C to 60°C Artikel-Nr. PPAS7207-1 CoreModule 3-BT4-ETT, PCI/104+ Single Board Computer, Intel Atom E3845 1.91GHz, up to 4GB DDR3L, -40°C to 85°C	Artikel-Nr. PPAS7205 CoreModule 3-BT1, PCI/104 Single Board Computer, Intel Atom E3815 1.46GHz, up to 4GB DDR3L, 0°C to 60°C Artikel-Nr. PPAS7205-1 CoreModule 3-BT1-ETT - PCI/104 Single Board Computer, Intel Atom E3815 1.46GHz, up to 4GB DDR3L, -40°C to 85°C

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

13 Artikel aus dem Bereich
PC/104 CPU Boards
wurden für das PDF ausgewählt.

Selection Guide PC/104 CPU Boards



CoreModule 2-BT2 PC/104+



CoreModule 1-BT1 PC/104



Musterartikel

TouchScreen	-	-	-
PC/104 (96 x 90 mm)	-	x	-
PC/104-Plus (96/99 x 90 mm)	x	-	-
PCI/104	-	-	-
PCI/104-Express (96/99 x 90/117mm)	-	-	-
PCle/104	-	-	-
Cooling System	-	-	-
CPU	Intel Atom E3825 (2C), 1.33 GHz	Intel Atom E3815 (1C), 1.46 GHz	-
CPU Socket	-	-	-
FSB Frequency	-	-	-
Chipset	-	-	-
BIOS	AMI EFI	AMI EFI	-
Watchdog Timer	x	-	-
Controller	SEMA Board Controller	SEMA Board Controller	-
Basic Equipment	-	-	-
Maximum Equipment	4GB	4GB	-
DRAM	-	-	-
SDRAM	-	-	-
DIMM / MemorySocket	DDR3L SO-DIMM	DDR3L SO-DIMM	-
CD-ROM	-	-	-
Compact Flash	-	-	-
SD	-	-	-
HDD	-	-	-
HD SATA	1x (optional 2nd SATA 3GB/s port)	1x	-
HD PATA	-	-	-
Removeable Storage	-	-	-
Graphic Interface	VGA/CRT, LCD-LVDS	VGA/CRT, LCD-LVDS	-
Interface COM	2x RS232/485, 2x RS232/485 (Optional)	2x RS232/485, 2x RS232/485 (Optional)	-
CAN	-	-	-
Interface USB	3x (1x on mSATA) USB 2.0	3x USB 2.0	-
Interface LAN	10/100/1000 BASE-T	10/100/1000 BASE-T	-
Interface IO	8x GPIO	8x GPIO	-
Mini PCIe	-	-	-
Mini PCI	-	-	-
Encoding	-	-	-
Decoding/Playback	-	-	-
Bluetooth	-	-	-
LPT	-	-	-
PS/2	-	-	-
Sound	ALC886	ALC886	-
Audio	-	-	-
Speakers	-	-	-
Headphone	-	-	-
Console Port	-	-	-
SIM Card	-	-	-
GPS	-	-	-
Mobile Communication 3G	-	-	-
PCI	-	-	-
PCle	-	-	-
ISA	-	-	-
PC/104	x	x	-
PC/104-Plus	-	-	-
PCI/104	-	-	-
PCI/104-Express	-	-	-
Video File Format	-	-	-
Max. Video Resolution	-	-	-
Operating System Support	Standard Support: Windows 7/8, 32/64-bit, Linux 32/64-bit, WES7/8, WEC7, QNX, VxWorks Extended Support (BSP): WES7/8, WEC7, Linux, QNX, VxWorks	Standard Support: Windows 7/8 32/64-bit, Linux 32/64-bit, WES7/8, WEC7, Linux, QNX, VxWorks	-
Input Voltage Nominal	5VDC	5VDC	-
Input Voltage Min/Max	-	-	-
Input Current	-	-	-
Power Management	-	-	-
Battery	-	-	-
Operating Temperature	0°C to 60°C	0°C to 60°C	-
Extended Operating Temperature	-40°C to 85°C	-40°C to 85°C	-
Storage Temperature	-	-	-
Relative Humidity	5-90% RH operating, non-condensing; 5-95% RH storage (and operating with conformal coating)	5-90% RH operating, non-condensing	-
MTBF	-	-	-
Certification	-	-	-
Dimensions	90 x 96mm	-	-
Weight	-	-	-
Typ. Application	Industrial	Industrial	-

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

13 Artikel aus dem Bereich
PC/104 CPU Boards
wurden für das PDF ausgewählt.

Selection Guide PC/104 CPU Boards



CoreModule 2-BT2 PC/104+



CoreModule 1-BT1 PC/104



Musterartikel

Bestellinformation	Artikel-Nr. PPAS7206 CoreModule 2-BT2, PC/104+ Single Board Computer, Atom E3825 1.33GHz, up to 4GB DDR3L, 0°C to 60°C Artikel-Nr. PPAS7206-1 CoreModule 2-BT2-ETT, PC/104+ Single Board Computer, Atom E3825 1.33GHz, up to 4GB DDR3L, -40°C to 85°C	Artikel-Nr. PPAS7204 CoreModule 1-BT1, PC/104 Single Board Computer, Intel Atom E3845 1.46GHz, up to 4GB DDR3L, 0°C to +60°C Artikel-Nr. PPAS7204-1 CoreModule 1-BT1-ETT, PC/104 Single Board Computer, Atom E3845 1.46GHz, up to 4GB DDR3L, -40°C to 85°C	Artikel-Nr. Artikelnr. Bezeichnung 1, Bezeichnung 2
--------------------	---	--	--

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

13 Artikel aus dem Bereich
PC/104 CPU Boards
wurden für das PDF ausgewählt.



Tiny-PPC837-666

TouchScreen	
PC/104 (96 x 90 mm)	-
PC/104-Plus (96/99 x 90 mm)	-
PCI/104	-
PCI/104-Express (96/99 x 90/117mm)	X
PCle/104	-
Cooling System	-
CPU	MPC8377E Power QUICC II Pro 667MHz
CPU Socket	-
FSB Frequency	133MHz
Chipset	-
BIOS	-
Watchdog Timer	-
Controller	-
Basic Equipment	512MB
Maximum Equipment	1GB
DRAM	-
SDRAM	DDR2
DIMM / MemorySocket	-
CD-ROM	-
Compact Flash	-
SD	1x
HDD	-
HD SATA	1x
HD PATA	1x 2GB PATA NAN Drive
Removeable Storage	-
Graphic Interface	-
Interface COM	1x RS232, 1x RS2422/485
CAN	-
Interface USB	1x Mini USB USB 2.0
Interface LAN	2x 10/100/1000 BASE-T
Interface IO	-
Mini PCle	-
Mini PCI	1x
Encoding	-
Decoding/Playback	-
Bluetooth	-
LPT	-
PS/2	-
Sound	-
Audio	-
Speakers	-
Headphone	-
Console Port	-
SIM Card	-
GPS	-
Mobile Communication 3G	-
PCI	-
PCle	-
ISA	-
PC/104	-
PC/104-Plus	-
PCI/104	1x
PCI/104-Express	-
Video File Format	
Max. Video Resolution	
Operating System Support	
Input Voltage Nominal	5VDC
Input Voltage Min/Max	-
Input Current	-
Power Management	-
Battery	-
Operating Temperature	0°C to 60°C
Extended Operating Temperature	-40°C to 85°C
Storage Temperature	-
Relative Humidity	5% to 95%
MTBF	-
Certification	-
Dimensions	-
Weight	-
Typ. Application	Industrial

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

13 Artikel aus dem Bereich
PC/104 CPU Boards
wurden für das PDF ausgewählt.



Tiny-PPC837-666

Bestellinformation

Artikel-Nr. PPAS6002

Tiny-PPC837-666/512-2G, PCI/104e SBC, 0°C to
60°C, MPC8377E CPU 667MHz, 512MB RAM,
2GB Storage

Artikel-Nr. PPAS6002-1

Tiny-PPC837-666/512-2G, PCI/104e SBC, -40°C to
85°C, MPC8377E CPU 667MHz, 512MB RAM,
2GB Storage

DELTA COMPONENTS GmbH

Auweg 27 * D-79761 Waldshut-Tiengen

Tel.: +49 (0) 7751 / 8399-0

Fax: +49 (0) 7751 / 8399-99

info@delta-components.de

<https://www.delta-components.de>

<https://www.automotive-computing.com>