

Selection Guide

Video Surveillance

DELTA COMPONENTS GmbH

Auweg 27 * D-79761 Waldshut-Tiengen

Tel.: +49 (0) 7751 / 8399-0

Fax: +49 (0) 7751 / 8399-99

info@delta-components.de

www.delta-components.de

www.automotive-computing.com

PDF Online Selection Guide
Stand vom 12.05.2024 - 01:00:36

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

3 Artikel aus dem Bereich
Video Surveillance
wurden für das PDF ausgewählt.



**MVS 5600-IP Modular Vehicle System
IP65**



MVS 5600 Modular Vehicle System



**MVS 2620-IP Modular Vehicle System
IP65**

Cooling System	Fanless	Fanless	Fanless
Mounting System	Wall Mount	Wall Mount	Wall Mount
CPU	6th gen Intel Core i7-6600U, 3.4GHz or i3-6100U, 2.3GHz, Skylake, Dual Core	6th generation Intel® Core dual core i7-6600U / i3-6100U	Intel Atom® x7-E3950 Apollo-lake 2.0GHz, Quad Core
Chipset	-	-	-
Basic Equipment	2GB	2GB	4GB
Maximum Equipment	8GB	16GB	8GB
SDRAM	-	-	-
DIMM / MemorySocket	DDR3L SO-DMIM	2-channel 204-pin DDR3L SO-DIMM	DDR3L SO-DMIM
Compact Flash	-	-	-
HDD	2x 2,5" SATA 3.0 HDD / SSD	1x 2,5" SATA 3.0 HDD / SSD (removable & hot swappable), RAID 0, 1 supported	2x 2,5" SATA 3.0 HDD / SSD
HD SATA	-	-	-
HD PATA	-	-	-
PCMCIA	-	-	-
Removeable Storage	-	-	-
Graphic Interface	1x VGA/CRT	1x VGA/CRT, 1x HDMI	1x VGA/CRT
Interface COM	2x RS232, 1x RS232, 2x RS485	1x DB-9 RS-232, 1x DB-9 RS-232, 1x DB-9 RS-232/422/485	2x RS232, 1x RS232, 2x RS485
CAN	1x CAN Bus 2.0B w/ isolation	1x CAN Bus 2.0B (on board)	1x CAN Bus 2.0B w/ isolation
CAN2	2x CAN Bus 2.0B (optional)	1x CAN Bus 2.0B (optional)	2x CAN Bus 2.0B (optional)
Interface USB	2x USB 2.0, 1x USB 3.0	4x USB 3.0	3x USB 2.0
Interface IEEE1394	-	-	-
Interface LAN	2x 10/100/1000 BASE-T, 2x WLAN	2x 10/100/1000 BASE-T, WLAN	2x 10/100/1000 BASE-T, 2x WLAN
Interface IO	3-bit GPO & 3-bit GPI GPIO, 3x Digital Input, 3x Digital Output	8x GPIO, 4x Digital Input, 4x Digital Output	3-bit GPO & 3-bit GPI GPIO, 3x Digital Input, 3x Digital Output
Mini PCIe	Mini-Pcie socket: 3x full size, 1x half size	Mini-Pcie socket: 2x full size, 1x half size	Mini-Pcie socket: 3x full size, 1x half size
Camera	-	-	-
Video Input	-	-	-
Resolution	Up to 2.560 x 1.600 @ 60Hz	Up to 2.560 x 1.600 @60Hz	Up to 2.560 x 1.600 @ 60Hz
Decoding/Playback	-	-	-
Codec	-	-	-
Bluetooth	-	-	-
eSATA	-	-	-
Sound	-	-	-
Audio	1x Mic-in, 1x Line-out	4x phone jacks 3,5 mm (2x Mic-in / 2x Line-out)	1x Mic-in, 1x Line-out
SIM Card	1x SIM card socket (w/ lid) & 1x internal SIM card socket selectable	1x externally accessible SIM card socket	1x SIM card socket (w/ lid) & 1x internal SIM card socket selectable
GPS	U-blox NEO-M8N	U-blox NEO-M8N	U-blox NEO-M8N
Mobile Communication 2G	-	-	-
Mobile Communication 3G	UMTS	-	UMTS
PCI	-	-	-
PCIe	4x Mini-Pcie socket	3x Mini-Pcie	4x Mini-Pcie socket
Operating System	Windows 10 / 8 / 7, WES8 / 7, Linux kernel 3.X	Windows 10 / Windows 8 / Windows 7 / WES8 / WES7 / Linux kernel 3.X	Windows 10 (64-bit only), Linux YOCTO
Input Voltage Min/Max	9 to 36VDC	9 to 36VDC	9 to 36VDC
Input Current	40W	34W	-
Battery	Optional internal 1.100mAh, Li-Polymer rechargeable battery	Optional internal 1100mAh, Li-Polymer rechargeable battery	-
Operating Temperature	-30°C to 60°C	-30°C to 60°C	-30°C to 70°C
Extended Operating Temperature	-	-	-
Storage Temperature	-40°C to 80°C	-40°C to 80°C	-40°C to 80°C
Relative Humidity	10% to 90% (non-condensing)	10% to 90% (non-condensing)	10% to 90% (non-condensing)
Protection	IP65, Vibration & Shock protection	Vibration & Shock protection	IP65, Vibration & Shock protection
Certification	CE, e13 (Vehicle), MIL-STD-810G, Class A FCC	CE, e13 (Vehicle), Class A FCC	CE, e13 (Vehicle), MIL-STD-810G, Class A FCC
Dimensions	260 x 196 x 66,5 mm (W x D x H)	260 x 196 x 66,5 mm (W x D x H)	260 x 196 x 50 mm (W x D x H)
Weight	3,3 kg	2,1 kg	2,88 kg
Material	-	-	-
Typ. Application	Industrial, Automotive, Mobile, Military, Outdoor	Industrial, Automotive, Mobile, Military, Outdoor	Industrial, Automotive, Mobile, Military, Outdoor

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

3 Artikel aus dem Bereich
Video Surveillance
wurden für das PDF ausgewählt.

Selection Guide Video Surveillance



**MVS 5600-IP Modular Vehicle System
IP65**



MVS 5600 Modular Vehicle System



**MVS 2620-IP Modular Vehicle System
IP65**

Bestellinformation

Artikel-Nr. PKBX5586-1

MVS 5600-7IPK Modular Vehicle System IP65,
Intel Core i3-6100U 2.3GHz, 2GB DDR3L, 2x GbE,
1x VGA

Artikel-Nr. PKBX5586

MVS 5600-3IPK Modular Vehicle System IP65,
Intel Core i7-6600U 3.4GHz, 2GB DDR3L, 2x GbE,
1x VGA

Artikel-Nr. PKBX5597

MVS 5600-7BU Modular Vehicle System, 6th Gen.
IntelCore i7-6600U, 2.6GHz, 2GB DDR3L, 2x GbE,
1x VGA/HDMI

Artikel-Nr. PKBX5597-1

MVS 5600-3BU Modular Vehicle System, 6th Gen.
IntelCore i3-6100U, 2.3GHz, 2GB DDR3L, 2x GbE,
1x VGA/HDMI

Artikel-Nr. PKBX5585

MVS 2620-IP Modular Vehicle System IP65, Intel
Atom x7-E3950 2.0GHz, QuadCore, 2x GbE, 1x
VGA

DELTA COMPONENTS GmbH

Auweg 27 * D-79761 Waldshut-Tiengen

Tel.: +49 (0) 7751 / 8399-0

Fax: +49 (0) 7751 / 8399-99

info@delta-components.de

<https://www.delta-components.de>

<https://www.automotive-computing.com>