

Selection Guide Firewire Module

DELTA COMPONENTS GmbH

Auweg 27 * D-79761 Waldshut-Tiengen

Tel.: +49 (0) 7751 / 8399-0

Fax: +49 (0) 7751 / 8399-99

info@delta-components.de

www.delta-components.de

www.automotive-computing.com

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

3 Artikel aus dem Bereich
Firewire Module
wurden für das PDF ausgewählt.

Selection Guide Firewire Module



FireSpeed2000

FIRE8000X

nanoFlame

Controller	-	-	x
IEEE1394a	3x IEEE1394a	3x IEEE1394b bilingual connectors	1x IEEE1394a
IEEE1394b	-	-	-
PCI	x	-	-
PCIe	-	x	mini PCIe
ISA	x	-	-
PC/104-Plus	x	-	-
PCI/104	-	pass-through (optional)	-
PCI/104-Express	-	-	-
Operating System Support	WIN, Linux	WIN, Linux	Windows, Linux, other drivers on request
Input Voltage Nominal	-	5V	-
Input Voltage Min/Max	-	External +12V	-
Input Power	-	-	-
Power Management	5V	-	-
Operating Temperature	0°C to 60°C	0°C to 60°C	-
Extended Operating Temperature	-40°C to 85°C	-40°C to 85°C	-40°C to 85°C
MTBF	-	-	-
Dimensions	90 x 96 mm	3,6" x 3,8"	-
Weight	-	-	-

Bestellinformation	Artikel-Nr. PPPF6012 FireSpeed2000, PC/104+ Board, 0°C to 60°C, IEEE-1394 FireWire controller Artikel-Nr. PPPF6012-1 FireSpeed2000-Ext., PC/104+ Board, -40°C to 85°C, IEEE-1394 FireWire controller	Artikel-Nr. PPPX6030-1 FIRE8000X-EXT, -40°C to +85°C, 3-port FireWire controller, PCI/104-Express	Artikel-Nr. PZIF3000-1 nanoFlame-Ext, IEEE-1394 Controller, -40C to +85C
--------------------	--	--	---

DELTA COMPONENTS GmbH

Auweg 27 * D-79761 Waldshut-Tiengen

Tel.: +49 (0) 7751 / 8399-0

Fax: +49 (0) 7751 / 8399-99

info@delta-components.de

<https://www.delta-components.de>

<https://www.automotive-computing.com>