

Selection Guide

Box Cameras

DELTA COMPONENTS GmbH

Auweg 27 * D-79761 Waldshut-Tiengen

Tel.: +49 (0) 7751 / 8399-0

Fax: +49 (0) 7751 / 8399-99

info@delta-components.de

www.delta-components.de

www.automotive-computing.com

Bitte laden Sie sich bei Bedarf [hier](#) eine aktualisierte Fassung dieses Dokuments herunter!

4 Artikel aus dem Bereich
Box Cameras
wurden für das PDF ausgewählt.

Selection Guide Box Cameras



IP Box Camera NCb-211



IP Box Camera NCb-221



IP Box Camera NCb-301

LCD Size			
Image Sensor	1/3" progressive scan CMOS sensor	Sony 1/2" Exmor image sensor	1/3" 3MP True WDR progressive scan CMOS sensor
Minimal Lux	B/W 0.01 lux / Color 0.1 lux	B/W 0.005 lux/Color 0.05 lux	B/W 0.01 lux / Color 0.1 lux
Lens	CS mount	-	Motorized (3-10mm, F1.4) lens
IrisType	DC Iris	-	P-Iris
Day + Night	x	Yes (with ICR & Light sensor)	x
IR Distance	-	-	-
IR Control	-	-	-
ICR	x	x	x
WDR	x	x	x
SD	-	-	-
Removeable Storage	Micro SD Slot	Micro SD Slot	Micro SD Slot
Internal Storage			
Graphic Interface	-	-	-
Interface COM			
Interface USB	-	-	-
Interface LAN	RJ45 10/100/1000 BASE-T, IEEE 802.3at PoE	RJ-45 10/100/1000 BASE-T, IEEE 802.3af PoE	RJ45 10/100/1000 BASE-T, IEEE 802.3at PoE
Interface IO	1x DI, 1x DO GPIO	1x DI, 1x DO GPIO	1x DI, 1x DO GPIO
Resolution	1920x1080@30 fps 1280x720@30 fps 720x576@30 fps 720x480@30 fps 640x480@30 fps 320x240@30 fps	1920 x 1080@30 fps 1280 x 720@30 fps 720 x 576@30 fps 720 x 480@30 fps 640 x 480@30 fps 320 x 240@30 fps	2048x1536@30 fps 1920x1080@60 fps 1280x720@30 fps 720x576@30 fps 720x480@30 fps 640x480@30 fps 320x240@30 fps
Processing	VBR/CBR	VBR/CBR	VBR/CBR
Codec	H.264 / M-JPEG	H.264/M-JPEG	H.264 / M-JPEG
Performance	Triple streaming H.264 Stream 1/ H.264 Stream 2/ MJPEG Stream 3	Dual-streaming	Triple streaming H.264 Stream 1/ H.264 Stream 2/ MJPEG Stream 3
Audio	1x 3.5mm phone jack	2x 3.5 mm phone jack	1x 3.5mm phone jack
Input Voltage Nominal	DC12V/AC 24V terminal block	DC 12V/AC 24V terminal block	DC12V/AC 24V terminal block
Input Current	-	-	-
Battery	-	-	-
Operating Temperature	0°C to 60°C	-20°C to 60°C	0°C to 60°C
Storage Temperature	-	-	-
Relative Humidity	90%, non-condensing	90% RH, non-condensing	90%, non-condensing
Protection	-	-	-
Certification	CE, FCC	CE, FCC	CE, FCC
Dimensions	126 x 73.27 x 64mm (D x W x H)	126 x 73.27 x 64 mm (D x W x H)	145 x 73.27 x 64mm (D x W x H)
Weight	-	470g	-
Typ. Application	-	-	-
Bestellinformation	Artikel-Nr. VKIX2000 IP Box Camera NCb-211, 0° C ~ 60° C, 2M, 1080P@30fps, H.264/ M-JPEG, DWDR, MicroSD, w/o Lens	Artikel-Nr. VKIX2003 IP Box Camera NCb-221, -20°C to 60°C, 2M, 1080P@30fps, H.264/ M-JPEG, DWDR, MicroSD, w/o Lens	Artikel-Nr. VKIX2001 IP Box Camera NCb-301, 0° C ~ 60° C, 3M, 1080P@60fps, H.264/ M-JPEG, trueWDR, MicroSD, w.L3-10m

Bitte laden Sie sich bei Bedarf [hier](#)
eine aktualisierte Fassung dieses
Dokuments herunter!

4 Artikel aus dem Bereich
Box Cameras
wurden für das PDF ausgewählt.



IP Box Camera NCB-311

LCD Size	
Image Sensor	1/3" 3MP progressive scan CMOS sensor
Minimal Lux	B/W 0.01 lux / Color 0.1 lux
Lens	CS mount
IrisType	DC-Iris
Day + Night	x
IR Distance	-
IR Control	-
ICR	x
WDR	x
SD	-
Removeable Storage	Micro SD Slot
Internal Storage	
Graphic Interface	-
Interface COM	
Interface USB	-
Interface LAN	RJ45 10/100/1000 BASE-T, IEEE 802.3at PoE
Interface IO	1x DI, 1x DO GPIO
Resolution	2048x1536@20 fps 1920x1080@30 fps 1280x720@30 fps 720x576@30 fps 720x480@30 fps 640x480@30 fps 320x240@30 fps
Processing	VBR/CBR
Codec	H.264 / M-JPEG
Performance	Triple streaming H.264 Stream 1/ H.264 Stream 2/ MJPEG Stream 3
Audio	1x 3.5mm phone jack
Input Voltage Nominal	DC12V/AC 24V terminal block
Input Current	-
Battery	-
Operating Temperature	0°C to 60°C
Storage Temperature	-
Relative Humidity	90%, non-condensing
Protection	-
Certification	CE, FCC
Dimensions	126 x 73.27 x 64mm (D x W x H)
Weight	-
Typ. Application	-

Bestellinformation	Artikel-Nr. VKIX2002 IP Box Camera NCB-311, 0° C ~ 60° C, 3M, 1080P@30fps, H.264/ M-JPEG, DWDR, MicroSD, w/o Lens
--------------------	--

DELTA COMPONENTS GmbH

Auweg 27 * D-79761 Waldshut-Tiengen

Tel.: +49 (0) 7751 / 8399-0

Fax: +49 (0) 7751 / 8399-99

info@delta-components.de

<https://www.delta-components.de>

<https://www.automotive-computing.com>